

# Technical data sheet for FAST FRI TWIN PAN ELECTRIC FRYER 450mm

FN8224E



- 17kW high performance twin pan fryer
- Easy clean stainless steel open pan with 10 year limited warranty
- 12L per pan oil capacity
- 25mm (1") drain valves
- Stainless steel exterior
- Easy service
- Fully modular
- Low back model (FNL) available

# **Overall Construction**

- Stainless steel pan with 10 year limited warranty
- Bull nose welded 1.5mm 304 stainless steel
- Splashback 1.5mm 304 stainless steel
- Side panels 1.2mm 304 stainless steel
- Double skin door with 0.9mm 304 stainless exterior
- Hinge out counterbalanced heating elements
- 25mm (1 ") drain valves
- 150mm legs in 63mm dia. heavy-duty 1.2mm 304 stainless steel with adjustable feet
- 2 baskets and stainless steel lid supplied standard

## Controls

- Mechanical thermostats
- Thermostat range 90-200°C
- Large easy use controls with easy view scale
- Fail-safe over-temperature safety cut-outs
- Element tilt switch for heating cut-out on element lift
- Indicator lights for power and heating (per pan)

# Cleaning and Servicing

- Open stainless steel pans for easy clean
- Easy clean basket support bar
- 25mm (1") drain valves for effective draining
- Easy clean stainless steel exterior
- Access to all parts from front of unit

# Technical data sheet for **FAST FRI TWIN PAN ELECTRIC FRYER** 450mm

## Specifications

**Production rate** 31kg/hr Pan Size (per pan) Oil capacity 12L (24lbs shortening) per pan Width 175mm Length 380mm Oil frying depth 95mm Baskets 2 chrome plated wire baskets 140mm W x 335mm D x 145mm H Elements (per pan) 3 x 2.83kW stainless steel heating elements **Electrical requirements** 17kW, 400-415Vac, 50/60hz, 3P+N+E L1 23.6A 12236A L3 23.6A

Electrical connection 62mm from RH side, 365mm from rear, and 440mm from floor

#### DIMENSIONS


Width 450mm Depth 805mm Height 915mm Incl. splashback 1130mm Incl. low back 1085mm


### NETT WEIGHT 74kg

PACKING DATA 0.54m3, 116kg Width 870mm Depth 495mm Height 1255mm

#### **OPTIONS AT EXTRA COST**

Waldorf Filtamax filtration system Extra baskets Side splash guards Joining caps Castors Plinth mounting







# MOFFAT

Australia www.moffat.com.au New Zealand www.moffat.co.nz

#### Australia Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

New South Wales Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia Telephone 03-9518 3888 vsales@moffat.com.au

Queensland Telephone 07-3630 8600 qldsales@moffat.com.au

#### Western Australia Telephone 08-9202 6820 bgarcia@moffat.com.au

New Zealand Moffat Limited

Christchurch Telephone 03-389 1007 sales@moffat.co.nz

Auckland Telephone 09-574 3150 sales@moffat.co.nz





Quality Management Standard

Designed and manufactured by MOFFAT,

ISO9001 All Waldorf products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

Printed in New Zealand © Copyright Moffat Limited Moffat/BH/6864

