



Food2Go

Active Cooling + Hot

Food2Go is a mobile serving platform for cook to serve applications. A perfect product when you need a versatile all-in-one product for transporting, holding and serving meals. The unit transports plates, single-portions, as well as containers. The spacious top surface fits up to three full size GN 1/1 containers with two GN 1/1 built-in ceramic heating plates to assure maintained temperatures during food service. Other features are adjustable ventilation for optimal moisture control, ergonomic push/pull handles and big castors for easy movement. A ScanBox is a Scandinavian designed product made for both back and front of house, especially with the Signature option with the possibility to customize the exterior design. Compressor cooling is standard and convection heating is offered as an option.

Outer Measurement		Inner Measurement	
Width	780 mm	Width	330 mm
Height	1357 mm	Height	576 mm
Depth	1320 mm	Depth (cold / hot)	596 / 553 mm

Capacity & Weight	
Capacity	7 + 7 x 1/1GN with 80 mm distance between runners
Maximum Loading Capacity / Runner	9 kg
Net Weight	140 kg
Volume	113 L Cold Chamber / 105 L Hot Chamber

Features	
Color	Black (RAL 9005) is standard. Red (RAL 3003) and Grey (RAL 7042). Free of charge.
Signature	Put your logo on the box or wrap it in your pattern.

Construction & Electrics

Interior	Anodized aluminium
Rack	Detachable laser cut U-shaped runners in SST
Exterior	Fiber glass plastic and aluminum profiles
Door Handle	One Grip Handle is standard
Door Opening	–
Chassi	Stainless Steel with rubber clad
Power Connection	220V-240V / 1 phase / 50-60Hz

Active Cooling

Compressor Cooling	Yes
Consumption W/A	221W / 0,96A
Temperature Range	+3°C to +10°C
DB / ΔT	63 / 30°

Totat W/A incl. hot plate	1150W / 5,0A
----------------------------------	--------------

Hot

Heating Element	Yes
Consumption W/A	453W / 1,97A
Temperature Range	Up to 90°C

Functions, Safety & Ergonomics

Digital Display	Yes, with temperature reached indicator
Adjustable Ventilation	Yes, open & close to adjust moisture level
Tray Stop	Protects from door scratches & trays moving
Runner Tilt Stop	Extra safety when loading/unloading the box
Classifications	CE, EMC, RoHS, REACH
Castors (standard)	Ø 160 mm double bearing (2 fixed, 2 swivel w/ brake)
Handles	Ergonomic push/pull handles
Extra Loading Spaces	–

Options

Tray Holder	Card Holders A4/A5/A6	Stainless Steel Interior
Tray Slide	Ergo Drive+ Motorized Chassi	
Condiment Holder	Ø 200mm Castors	
Dustbin Holder	Tow Bars	
Countertop Slots	Customized Spacing for Runners	
One Grip Handle w. Lock Key	Pressed Runners	

For detailed information of available options please refer to scanbox.se