

BAKERY RANGE



YOU MAKE THE DOUGH WHILE WE SAVE YOU DOUGH

Since 1981 Starline warewashers have been engineered specifically for New Zealand conditions and are supported nationwide by the best service network in the industry.

Washtech Warewashers:

- Provide unrivalled product reliability and longevity;
- Are hand made from heavy duty stainless steel;
- Feature intuitive controls with easy to read displays;
- Are constructed locally to be easy to maintain and service;
- Can be customised to your requirements; and,
- Have multiple cycle options for various wash needs.
- Heat Recovery solutions available on select models, providing reductions in emissions and operating costs.

Talk to a Starline dealer today about how the latest warewashing solutions will benefit you and your customers



PW2

Componentry	Heavy duty stainless steel
Wash power	4.0HP
Capacity	480 baking trays per hour
Chamber size	Width: 1100mm Depth: 50mm Height: 750mm

STARLINE
PROFESSIONAL WASH SYSTEMS



0800 503 335



www.southernhospitality.co.nz

BAKERY RANGE

TW AL8 PW1 PW2 PW3 CK100



Standard cycle times (seconds)	120	120, 240, 360	120, 240, 360	120, 240, 360	120, 240, 360	continuous
Bakery trays per hour* (up to 40mm deep)	120		240	480		
Wash pump power (HP)	2 x 0.5	2.0	2.0	2 x 2.0	2 x 2.0	2.0
External dimensions:						
width (mm)	860	905	680	1235	1330	1500+
depth (mm)	660	760	780	855	855	875+
height (mm)	845	1750	1850	1850	1750	1585+
Bench gap	865	795	680	1235	1195	1500+
Internal dimensions:						
width (mm)	800	700	565	1100	1050	620
depth (mm)	545	540	595	650	640	variable
height (mm)	470	650	750	750	650	450 to 800
Dual chemical pumps (externally adjustable det. and rinse fluid pumps)	Y	Y	Y	Y	Y	
Full stainless steel componentry	Y	Y	Y	Y	Y	Y
Enhanced stainless steel filtration (scrap trays in addition to wash inlet filter)	Y	Y	Y	Y	Y	Y
Heat recovery unit (reduce emission and operating costs)		Optional	Optional	Optional	Optional	Optional
Break tank and rinse pump fitted (suitable for sites with low water temp and pressure)		Y	Y	Y	Y	Optional
Drain pump installed	Y	Optional	Optional	Optional	Optional	
Hot water consumption (litres) (per cycle)	3.3	2.7	2.7	4.0	4.0	5.0 (per minute)
Power requirements (higher ratings improve rinse recovery time)	1p/15A	3p/25A	3p/25A	3p/30A	3p/30A	3p/25A (base machine only)
List price (\$) (excluding GST)	12,500	13,500	14,500	21,900	26,900	POA

*Bakery trays per hour based on 35mm deep trays equivalents, and 80% operational efficiency through the Potwasher



0800 503 335



www.southernhospitality.co.nz