

# PLANET TECHNOLOGY – M2C



## ANNUAL POWER SAVINGS IN EXCESS OF \$1k AND NO EXTRACTION CANOPY REQUIRED

Making the right choice for the planet has never been as easy, or as good for your bottom line.

By recovering the heat from the steam generated during the operation of the dishwasher to heat the incoming rinse water, the Starline M2C will provide your establishment with:

- ✓ Significant reductions in operating costs in excess of \$1,000 per year\*
- ✓ Considerable reduction in steam emissions which eliminates the need for an extraction canopy\*\*.

### Additional Benefits:

- Improved operating environment: Drawing air from the machine during the cycle ensures minimal emissions during the cycle and when the hood is opened.
- Same great dishwasher: The M2C is constructed from heavy duty stainless steel and will provide excellent wash results year-after-year, as per the renowned M2.
- Lower cost water treatment options: The cold inlet water required by the M2C is cheaper and easier to treat than a hot water supply.
- Polish-free glasswasher: Operating 60 second cycles efficiently on cold water and providing accelerated drying results makes the M2C a ideal part of a high capacity polish-free glasswashing system.

**STARLINE**  
PROFESSIONAL WASH SYSTEMS

\*Savings calculations assume 20 °C inlet temperature, with 20 medium cycles run per hour, 8 hours per day, 360 days per annum, at average power cost of \$0.20 per kWh.

\*\*Full certification from SEED is available on request.



0800 503 335



[www.southernhospitality.co.nz](http://www.southernhospitality.co.nz)

# M2C vs M2

## Energy Consumption Comparison

### Indicative and for Discussion Purposes only

#### Assumptions:

Days usage per annum	360
Hours operation per day	8
Average cycles per hour	20
Power cost (kWh)	\$0.20



**Starline M2**  
Standard  
Hot Water  
3 Phase/15 Amp  
1/2/3 minute cycles  
Canopy Required



**Starline M2C**  
Heat Recovery  
Cold Water  
3 Phase/15 Amp  
1/2/3 minute cycles  
Canopy not required\*

#### Rinse Water Usage (per day):

Water consumption per cycle (L)	2.4	2.4
Total water usage per hour (L)	48	48
Total water usage per day (L)	384	384

#### Rinse Water Heating (per day):

Onsite heating to 65°C (from 20°C)	21.27	
Standard machine heating to 83°C **	13.24	
Dishwasher with HRU to 83°C ***		20.33

Daily Rinse Water Heating Cost: \$ 6.90 \$ 4.07

Annual Rinse Water Heating Cost: \$ 2,484.00 \$ 1,463.00

**Forecast Annual Cost Savings: \$ 1,021.00**

**Forecast 10-Year Cost Savings: \$10,210.00**

#### Plus: Reduced Cost of Extraction:

\$ \_\_\_\_\_

The M2C emits significantly less steam and is certified for installation without an extraction canopy.

#### Plus: Reduced Cost of Water Treatment:

\$ \_\_\_\_\_

It is generally more economical to treat cold water, making dishwashers with HRUs plus a softening system ideal for hard water sites.

#### Total Forecast Savings For Your Restaurant:

\$ \_\_\_\_\_

This is intended as an indicative analysis of the potential differences in operating costs for discussion purposes only. The total operating cost of both models will be higher once the water used to fill the machine and wash heating etc. are accounted for.

\*SEED certified for installation without a canopy in most locations. Certification available on request.

\*\*Reduction in inlet temp between onsite heating and dishwasher will vary due to a number of factors. In this example it is assumed to be 10°.

\*\*\*In factory trials the Washtech M2C HRU produces >20° of heating from a 20° cold water supply when operating on the medium cycle.

