

NU 300 XSafe

Self Contained Ice Machine 142 kg

Item #:
Project:
Quantity:



FEATURES

- Front-in & front-out air flow: no need to leave space on the back.
- Resistant stainless steel exterior.
- High grade appearance.
- Front access condenser air filter: a do-it-yourself cleaning operation that saves time and money and makes your ice maker live longer.
- Ergonomic access to ice with sliding disappearing door: one touch door lift makes barman's life significantly easier.
- One touch cleaning: reduces labor costs and saves time and simplifies cleaning process.
- Routine Maintenance visible alarm light on front panel.
- Built-in storage bin: allows undercounter installations for easier fit-in solution, specifically for coffee shops.
- XSafe: natural sanitation system, integrated inside the ice maker and operating automatically 24/7 to keep equipment clean & safe.



NU 300
Dice 10 g
W 22 x D 22 x H 22 mm



NU H 300
Half Dice 6 g
W 10 x D 22 x H 28 mm



NU L 300
Large Dice 15 g
W 28 x D 22 x H 28 mm

CONDENSING SYSTEM

Air cooled
Water cooled

REFRIGERANT GAS

R404A
R452A

VOLTAGE V/Hz/ph

230/50/1

INTERNAL BIN CAPACITY

37 kg

CERTIFICATIONS



OPERATING REQUIREMENTS

	Minimum	Maximum
Air temperature	10	40
Water temperature	5	35
Water pressure	1 bar (14 psi)	5 bar (70 psi)
Electrical voltage	-10%	+10%

IMPORTANT NOTICE:
Models and specifications are subject to change without notice.
This spec sheet is meant for commercial purpose only.
For technical documentation please refer to our service manuals.

www.scotsman-ice.it
www.scotsman-ice.com


Self Contained Ice Machine 142 kg

NU 300 XSafe

Self Contained Ice Machine 142 kg

Item #:
Project:
Quantity:

Self Contained Ice Machine 142 kg



UNIT DATA		SHIPPING DATA		(*) Data refer to 32°C Amb. / 21°C Water temperature conditions							
Size (W x D x H)		650 x 690 x 1003 mm		Carton (W x D x H)		730 x 770 x 1050 mm					
Net weight		65 kg		Weight		77 kg					
Version	Voltage	24 h ice production kg °C Amb. / °C Water			Energy consumption (*)		Water usage (*)	Instant power	Compressor	Circuit wires	Max. fuse size
		10°C/10°C kg	21°C/10°C kg	32°C/21°C kg	kWh/ 100 kg	kWh/ 24h	l/h	W	W	No. x Ømm ²	A
NUH 300 AS	230/50/1	128	121	92	17.6	16.2	5.7	950	1767	3 x 1.5	16
NUH 300 WS	230/50/1	130	130	115	12.1	13.9	89.8	950	1767	3 x 1.5	16
NUL 300 AS	230/50/1	142	130	93	17.6	16.4	5.8	950	1767	3 x 1.5	16
NUL 300 WS	230/50/1	142	130	100	12.1	12.1	78.1	950	1767	3 x 1.5	16
NU 300 AS	230/50/1	142	135	100	17.6	17.6	6.2	950	1767	3 x 1.5	16
NU 300 WS	230/50/1	135	130	115	12.1	13.9	89.8	950	1767	3 x 1.5	16