

SM2-25W, SM2-251PW, SM2-50TW, SM2-80TW, SM2-120TW

Spiral Mixers

Product Features

- 25, 50, 80 or 120kg dough capacity
- Fitted with a breaker bar & wire grid guard
- 2 speed electronic controls on all models
- Designed for the busy retail bakery
- 4 lock down feet supplied as standard
- Micro-switch controlled bowl guard
- 50,80 & 120kg models fitted with bowl reverse function
- Heavy-duty construction
- Fitted with manual operation override switch
- Finished in 2 pak paint for superior wear resistance
- Optional fully enclosed guards available on request



SM2-80TW



SM2-25W

Paramount spiral mixers are designed to withstand the demands of high production bakery. The structure is fabricated from heavy gauge steel and 2 pak painted for high wear resistance. The mixers are fitted with an electronic control panel which provides options for slow speed mixing in forward or reverse direction, high speed mixing in forward direction, and incorporates a bowl jog feature to allow easy removal of dough. The wire grid guard is designed for complete operator safety, but still allows easy visibility of the dough while mixing.

SM2-25W, SM2-251PW, SM2-50TW, SM2-80TW, SM2-120TW

Spiral Mixers

Model SM2-25W

Dough capacity 25kg
Flour capacity 12.5kg
Dimensions
Width 560mm
Depth 850mm
Height 1120mm
Electrical Requirements
400-415V, 3P+E, 2.20kW
4 pin 10amp plug
Nett Weight 135kg

Model SM2-251PW

Dough capacity 25kg
Flour capacity 12.5kg
Dimensions
Width 560mm
Depth 850mm
Height 1120mm
Electrical Requirements
240-415V, 1P+N+E, 50Hz
3 pin 10amp plug
Nett Weight 135kg

Model SM2-50TW

Dough capacity 50kg
Flour capacity 25kg
Dimensions
Width 640mm
Depth 1080mm
Height 1220mm
Electrical Requirements
400-415V, 3P+E, 3.75kW
4 pin 10amp plug
Nett Weight 320kg

Model SM2-80TW

Dough capacity 80kg
Flour capacity 50kg
Dimensions
Width 765mm
Depth 1280mm
Height 1330mm
Electrical Requirements
400-415V, 3P+E, 5.25kW
4 pin 20amp plug
Nett Weight 385kg

Model SM2-120TW

Dough capacity 120kg
Flour capacity 75kg
Dimensions
Width 825mm
Depth 1470mm
Height 1520mm
Electrical Requirements
400-415V, 3P+E, 9.55kW
4 pin 20amp plug
Nett Weight 610kg

moffat.com.au

moffat.co.nz

Australia

moffat.com.au

Moffat Pty Limited

Victoria/Tasmania

740 Springvale Road
Mulgrave, Victoria 3170
Telephone +613-9518 3888
Facsimile +613-9518 3833
vsales@moffat.com.au

New South Wales

Telephone +612-8833 4111
nswsales@moffat.com.au

South Australia

Telephone +613-9518 3888
vsales@moffat.com.au

Queensland

Telephone +617-3630 8600
qldsales@moffat.com.au

Western Australia

Telephone +618-9413 2400
wasales@moffat.com.au

New Zealand

moffat.co.nz

Moffat Limited

Rolleston

45 Illinois Drive
Izone Business Hub
Rolleston 7675
Telephone +64 3-983 6600
Facsimile +64 3-983 6660
sales@moffat.co.nz

Auckland

Telephone +64 9-574 3150
sales@moffat.co.nz



Electronic controls



Wire guard



In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd
AN.P.01.20

an Ali Group Company



The Spirit of Excellence