

Four Glass Sliding Door SlimLine

Range: BackBar
SKOPE ID: SL014
Dimensions: 2800 mm (W) × 600 mm (D) × 830 mm (H)*
Capacity: 606 L

Project: _____


Item #: _____

* Height with castors is adjustable from 820 to 835.



A glass door under-counter bar fridge designed to merchandise ready-to-serve cold beverages in bars, restaurants, clubs, pubs, and cafés. Engineered to serve cold drinks at 1°C to 4°C (or adjustable up to 15°C) in ambient environments of up to 32°C. Made from powder-coated, galvanised steel with colour options, it can also be upgraded to full stainless-steel construction. The glass doors are designed for condensation protection in most environments via the double-glazed, argon-filled low-e insulated panels and heated fascia. Sliding door locks are optional. The built-in LED lights provide optimum merchandising and can be dimmed or timed to turn on and off via a free smartphone app. The fridge uses R290 natural refrigerant for ultra-low-energy consumption, low heat discharge and low noise output and can be provided in remote versions. The side-mounted fully removable refrigeration cartridge (with left and right options) is front-breathing and can be removed in line with best practice for safe servicing of flammable refrigerants. The fridge includes a controller that connects to a free app to enable the user to set temperatures and alerts, monitor temperatures and energy, and more. The fridge is certified to all Australian and New Zealand refrigeration and electrical safety standards.





Cabinet

Type	SlimLine		
Finish	Powdercoat galvanised steel or stainless steel		
Insulation	Type	PU foam	
	Thickness (mm)	50	
	Blowing Agent	Cyclo-iso pentane (C5H10/C5H12)	
Doors	Type	Glass sliding door (double glazed, low-e, argon filled)	
	Opening Size	Height (mm)	538
		Width (mm)	511
Shelving	Eight adjustable height plastic-coated wire shelves 4 × outer shelf (547W × 440D), 4 × inner shelf (605W × 440D)		
Lighting*	2 × 16 W, cool white (5500-6500K) LED strips on cabinet ceiling		

Dimensions†

	External	Internal	Packed
Width (mm)	2800	2340	TBC
Depth (mm)	600	475	TBC
Height (mm)	830 (std. castors)	545	TBC
	725 (plinth mount)		
Weight (kg)	255		TBC
Capacity (L)	606		
Footprint (m²)	1.68		

Ventilation (mm)

Top	Not required	Sides	Not required	Rear	Not required
-----	--------------	-------	--------------	------	--------------

Product Loading

Facing	330 ml can	68	600 ml bottle	60
Loading	330 ml can	408	600 ml bottle	360

* Accessible via the free SKOPE-connect™ app.

† Allow for dimensional tolerances when installing the cabinet(s).

Performance

Product Temperature Range (°C)	1 to 4 (adjustable* from 0 to 15)	
Maximum Ambient Temperature (°C)	32	
Sound Level (dB(A))	Standard	< 66
	Hush Mode*	< 62

Greenhouse and Energy Minimum Standards (GEMS)

Star Rating	4	
Product Temperature Class	M1 (-1 to 5°C)	
Total Energy Consumption	8.24 kWh/24 h	
Annual Running Costs	\$902 (@ \$0.30/kWh)	

Electrical

Supply	220-240 volts a.c., 50 Hz, single phase supply	
Cord	1.9 m power cord with 3-pin, 10 amp plug	
Current draw (A)	4	

Refrigeration

Controller	SCS Connect (SKOPE-connect™ compatible)		
System Type	Removable cartridge		
Cartridge Weight (kg)	24		
Refrigerant/Charge	R290/81 g		
Nominal Capacity (W)	850		
Heat Rejection (W)	Average	345	Peak 360
Defrost Type	Automatic, off-cycle		
Drainage	No plumbing required		



SL.4.GSL
on the SKOPE website