

Stable doors for efficiency of cold air retention



Strong stainless steel hinges and self closing doors



Door locks as standard



Compact Upright Range



This range from EuroChill has a stylish modern design. It is ergonomically engineered for practical and user friendly operation. This compact size is perfect for any kitchen area restricted by size constraints without wanting to compromise on aesthetics, quality and performance. Available in both single and double door. Refrigerator and freezer options, as well as a dual temperature model. 2 year warranty* on chillers and freezers.





OTHER FEATURES



- Top mounted compressor easily removed for repairs or replacement
- Stable doors for efficiency of cold air retention
- Recessed door handles



- · Coved internal cavity for easy cleaning
- High density, CFC free polyurethane insulation for the entire cabinet structure and door



- Stainless steel interior and exterior, galvanized backing
- Digital temperature control
- · Automatic on/off evaporator fan with door opening
- Self closing doors
- Strong stainless steel door hinges
- · Door locks come as standard
- Comes on castors
- · 2 year warranty

Model	ERE50 Single Stable Door Chiller	ERE52 Single Stable Door Freezer	ERE51 Double Stable Door Chiller	ERE53 Double Stable Door Freezer	ERE54 Dual Temp Stable Door Fridge/ Freezer
Dimensions	600W x 745D x 1950mmH	600W x 745D x 1950mmH	1200W x 745D x 1950mmH	1200W x 745D x 1950mmH	1200W x 745D x 1950mmH
Capacity	370L	370L	900L	900L	855L
Operating Temp	−2 ~ 8°C at 43°C ambient	−22 ~ −17°C at 43°C ambient	−2 ~ 8°C at 43°C ambient	−22 ~ −17°C at 43°C ambient	-2~8°C at 43°C ambient/ -22 ~ -17°C at 43°C ambient
No of shelves	3 plus floor	3 plus floor	3 plus floor per side	3 plus floor per side	3 plus floor per side
Material	Stainless steel with galvanised backing				
Insulation	Polyurethane	Polyurethane	Polyurethane	Polyurethane	Polyurethane
Refrigerant	R600a	R290	R600a	R290	R600a
Voltage	220V / 50Hz				
Imput Power	.3kW, 10amp plug	0.5kW, 10amp plug	.4kW, 10amp plug	.7kW, 10amp plug	.7kW, 10amp plug
Weight	90kg	90kg	135kg	135kg	135kg

^{*2} year warranty subject to proper maintenance and use.
Sufficient ventilation required. See EuroChill warranty document for more information.

• Subject to correct use and maintenance. Specifications are subject to change without notice.

EuroChill Manufacturing
Distributed by Southern Hospitality Ltd 0800 503 335
www.southernhospitality.co.nz

