

2 YEAR
WARRANTY



Strong stainless steel hinges and self closing doors



Wide doors for café trays



Comes on castors



Recessed door handles

EUROCHILL

Summit Undercounter Range



EuroChill's Summit Undercounter range gives you quality refrigeration with style and performance. A sleek, modern look and designed with practicality and ergonomics in mind. This range would suit any commercial kitchen with undercounter refrigeration or freezing requirements. Sizes from 1200mm, 1500mm and 1800mm in freezer and refrigerator options. 2 year warranty* on chillers and freezers. High performance compressors ensure these units are rated to run at an ambient temperature of up to 43°C.

KEY FEATURES



- Maximized and convenient storage capacity
- Wide doors on larger models for easy access of trays
- Recessed door handles
- Left hand side mounted compressor
- Coved internal cavity and drain for easy cleaning
- High density, CFC free polyurethane insulation for the entire cabinet structure and door
- Stainless steel interior and exterior, galvanized backing
- Digital temperature control
- Self closing / stay open doors
- Adjustable shelving
- Strong stainless steel door hinges
- Comes on castors
- 2 year warranty*

Model	ERE56 2 Door Chiller	ERE60 2 Door Freezer	ERE57 2 Door Chiller	ERE61 2 Door Freezer	ERE58 3 Door Chiller	ERE62 3 Door Freezer
Dimensions	1200W x 700D x 840mmH	1200W x 700D x 840mmH	1500W x 700D x 840mmH	1500W x 700D x 840mmH	1800W x 700D x 840mmH	1800W x 700D x 840mmH
Capacity	270L	270L	370L	370L	470L	470L
Operating Temp	-2 ~ 8°C at 43°C ambient	-22 ~ -12°C at 43°C ambient	-2 ~ 8°C at 43°C ambient	-22 ~ -12°C at 43°C ambient	-2 ~ 8°C at 43°C ambient	-22 ~ -12°C at 43°C ambient
No of shelves	1 per door	1 per door	1 per door	1 per door	1 per door	1 per door
Material	Stainless steel with galvanised backing	Stainless steel with galvanised backing	Stainless steel with galvanised backing	Stainless steel with galvanised backing	Stainless steel with galvanised backing	Stainless steel with galvanised backing
Insulation	Polyurethane	Polyurethane	Polyurethane	Polyurethane	Polyurethane	Polyurethane
Cooling Type	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated
Refrigerant	R600a	R290	R600a	R290	R600a	R290
Voltage	220V / 50Hz	220V / 50Hz	220V / 50Hz	220V / 50Hz	220V / 50Hz	220V / 50Hz
Input Power	.3kW, 10amp plug	.45kW, 10amp plug	.38kW, 10amp plug	.55kW, 10amp plug	.38kW, 10amp plug	.55kW, 10amp plug
Weight	79kg	79kg	85kg	85kg	91kg	91kg

*2 year warranty subject to proper maintenance and use.

Sufficient ventilation required. See EuroChill warranty document for more information.


• Subject to correct use and maintenance. Specifications are subject to change without notice.

EuroChill Manufacturing


Distributed by Southern Hospitality Ltd 0800 503 335

www.southernhospitality.co.nz

ERE56
ERE60




BIRDS EYE VIEW




FRONT VIEW

ERE57
ERE61




BIRDS EYE VIEW




FRONT VIEW

ERE58
ERE62



BIRDS EYE VIEW



FRONT VIEW