



RIGID CAST
IRON BODY

NON-SLIP
RUBBER
FEET

DELTA PLANETARY MIXER 60 LITRE

ED60

SPECIFICATIONS

- Capacity: 60 litre stainless steel bowl
- Dimensions: 780mm (L) x 650mm (W) x 1310mm (H)
- Weight: 310kg
- Power: 400V/50Hz, 2.2KW, 3 phase / Plug Not supplied
- Speeds: low speed 99rpm, intermediate speed 176rpm, high speed 320rpm
- Shipping Information:
- Net Weight: 270kgs
- Gross Weight: 310kgs
- 6-foot cord, no plug
- Cartons are affixed to an undersized skid (pallet), the weight and dimensions of this skid are not included and may vary from shipment to shipment.

Complete with:

- 60 Litre stainless steel bowl
- Flat beater (aluminium)
- Wire whip (Stainless steel)
- Spiral dough hook (aluminium)
- Bowl truck

FEATURES & BENEFITS

- Delta Mixer controls are front-mounted to give easy access in cramped kitchen environments. The following controls are standard on all Delta Mixers: separate start and emergency stop buttons, so operators can shut down the mixer immediately in an emergency situation and thermal overload protection.
- Heat-treated, hardened alloy, precision milled gears operate with planetary action. Gears are packed in a long-lasting, high pressure grease. Planetary gears are driven by an oversized cog-wheel, which is in turn driven by a cogged belt powered by the motor drive shaft. Cogged belt is a long-lasting, rugged fibre/rubber composite. This unique design yields high-torque mixing power while avoiding the high

cost encountered repairing direct-drive transmission components.

- Bowls & Agitators: Standard equipment includes a 60 Litre high-quality stainless-steel bowl, dough hook, flat beater, and whip. A sturdy hand lever on the body column raises and lowers the bowl as well as locking in place at the top and bottom positions.
- 15-minute timer which shuts off the machine after set time has elapsed.
- Heat-treated hardened steel alloy gears and shafts
- Permanently lubricated transmission.
- Stainless steel bowl guard with built in ingredient chute.
- Industry standard No.12 attachment hub.
- Safety interlocked bowl guard and bowl lift.

ED60

• Specifications are subject to change without notice. Subject to correct use and maintenance.