










C10.1
Cod: C10.1












STANDARD EQUIPMENT

	Air condensing unit	Built-in
	Door hinges	Left
	Refrigerant gas	Included
	Suitable for	Combi GN1.1/60x40
	Adjustable tray distance	30 mm
	Cabinet installation	Feet
	Core probe	Included
	Packaging	Pallet+bubble wrap
	Stainless steel guides	10

TECHNICAL DATA

Yield +90°C -> +3°C/-18°C (Kg)	50
Range (°C)	-40/+3
Capacity GN1.1 / 600x400 (h65, h40, h20)	8-12-25
Capacity ice cream 330x165x120h	15
Trays pitch (mm)	30
Power 400 V 3ph+N 50hz (kW ; A)	2,9 ; 6
Power 440 V 3ph+N 60hz (kW ; A)	2,9 ; 6,6
Power 230 V 3ph 60hz (KW ; A)	2,9 ; 12,5
Refr. Yield (kW Tev=-10; Tc=+40°C) / HP	4.1 /
Refrigerant gas	R452a / R449a
Cabinet size (WDH)	800 x 813 x 1560
Cabinet (indicative) packed size (WDH)	1000 x 1025 x 1905
Weight: cabinet/condensing unit (kg)	180 / 0
Weight packed: cabinet/condensing unit (kg)	195 / 0
Evaporator fan max. air flow (m³/h)	3300
Minimum air circulation request (m³/h)	3200
Working conditions (°C/Ur%)	32/55
Ventilator diameter (mm)	300
Evaporator surface (m²)	12
Compressor Brand	Tecumseh / Maneurop

UNIQUE FEATURES

	VENTILATION SYSTEM: Bionic Blade		SERVICE & HACCP Only USB: 260 €
	EVAPORATOR: Evaporator XL surface: big surface able to quickly remove the heat		CONSTRUCTION: 60 mm panels, 90 mm top part, 45kg/m³ polyurethane foam. Stainless steel AISI 304 Inside and outside
	EXPANSION VALVE: Thermal		CIRCUIT PROTECTION: Evaporator and Condenser protected with cataphoresis treatment
	AIR CONTROL: AIR PLUS SYSTEM: +20% efficiency (Pressure, Largeness, Uniformity, Speed)		DOOR CLOSER: Automatic closing
	DISPLAY: Digital		REFRIGERANT GAS: R452a / R449a
	CONTROL BOARD: Electrical board		